



Print Date:	05/01/2024	<b>Specification Log Number</b>			<b>24C55</b>	
<b>Specification &amp; Product Information Sheet</b>						
Product Name	Wrapmaster 4500 Aluminium Foil Refill Rolls			Product Code	24C55	
Material	Aluminium Foil, in compliance with Regulation 1935/2004/EC on materials and articles intended to come into contact with food.					
Roll Dimensions	Length	90mtrs (+/- 2.5%)	Width	445 - 455mm	Micron	9 - 11 micron
Labels Inner	Label to be used on each roll to secure the foil.			Labels Outer	Two labels to be applied to the outer case as follows: One Label containing Product code/Description/Barcode/Qty & MPRD/Date-code. One label stating Country of Origin as per Raw Material Used.	
Country Of Origin & Manufacture	Country of Origin China. Manufactured in the UK.			Barcode Single	N/A	
Core Size	58T21 - 462mm x 30mm x 3mm + 60M98A Black Plastic Bung			Barcode Pack	N/A	
Packaging Inner Box	N/A			Barcode Case	5023139245536	
Packaging Outer Box	Wrapmaster 4500 printed cardboard box			Specification Instructions	61M11 security label must be used to ensure that the box stays closed.	
<b>Packing Instructions</b>				<b>Pallet Configuration</b>		
Pack 3 rolls per outer case				Standard/CHEP Pallet - 13 Cases Per Layer, 7 Layers high + 9 on top, 100 Cases Per Pallet. Euro pallet - 9 Cases Per Layer, 8 Layers high, 72 cases per pallet.		
<b>Weights &amp; Dimensions (Approximate)</b>		<b>Packaging Waste Weights (Approximate) (G)</b>				
		<b>Primary Packaging</b>	<b>Secondary</b>	<b>Secondary</b>	<b>Transit</b>	
Inner Weight (G) (Gross)	N/A	Recycled Cardboard/Paper	225	0	0	1130
Pack Weight (G) (Gross)	N/A	Recycled Cardboard/paper Core	290.5	0	0	0
Case Weight (KG) (Gross)	3.8	Plastic LDPE	0	0	0	415
Inner Dimensions (CM) W x H x D	N/A	Plastic PP	21.9	0	0	0
Pack Dimensions (CM) W x H x D	N/A	Plastic Blade	0	0	0	0
Case Dimensions (CM) W x H x D	52.2 x 6 x 16.5	Metal Blade	0	0	0	0
<b>Intrastat/Commodity Code</b>						
76071111						
<b>Pallet Wrapping</b>						
Cardboard corner to be placed on each corner of the pallet & Stretch wrapped secured to pallet, minimum of 8 revolutions						